

UTILITY PATENT APPLICATION TRANSMITTAL

Attorney Docket No.

First Named Inventor or Application Identifier:

Masahiro ICHIMI

Express Mail Label No.

Only for new nonprovisional applications under 37 CFR 1.53(b))

APPLICATION ELEMENTS

See MPEP chapter 600 concerning utility patent application contents.

ADDRESS TO:

**Assistant Commissioner for Patents
Box Patent Application
Washington, DC 20231**

1. ☒ Fee Transmittal Form
2. ☒ Specification, Claims & Abstract [Total Pages: 13]
3. ☒ Drawing(s) (35 USC 113) [Total Sheets: 8]
4. ☒ Oath or Declaration [Total Pages: 3]
 - a. ☒ Newly executed (original or copy)
 - b. ☐ Copy from a prior application (37 CFR 1.63(d)) (for continuation/divisional with Box 17 completed)
 - i. ☐ DELETION OF INVENTOR(S)
Signed statement attached deleting inventor(s) named in the prior application, see 37 CFR 1.63(d)(2) and 1.33(b)
5. ☐ Incorporation by Reference (usable if Box 4b is checked)
The entire disclosure of the prior application, from which a copy of the oath or declaration is supplied under Box 4b, is considered as being part of the disclosure of the accompanying application and is hereby incorporated by reference therein.
6. ☐ Microfiche Computer Program (Appendix)
7. ☐ Nucleotide and/or Amino Acid Sequence Submission (if applicable, all necessary)
 - a. ☐ Computer Readable Copy
 - b. ☐ Paper Copy (identical to computer copy)
 - c. ☐ Statement verifying identity of above copies

ACCOMPANYING APPLICATION PARTS

8. ☒ Assignment Papers (cover sheet & document(s))
9. ☐ 37 CFR 3.73(b) Statement (when there is an assignee) [] Power of Attorney
10. ☐ English Translation Document (if applicable)
11. ☐ Information Disclosure Statement (IDS)/PTO-1449 [] Copies of IDS Citations
12. ☐ Preliminary Amendment
13. ☒ Return Receipt Postcard (MPEP 503) (Should be specifically itemized)
14. ☐ Small Entity Statement(s) [] Statement filed in prior application, status still proper and desired.
15. ☒ Certified Copy of Priority Document(s) (if foreign priority is claimed)
16. ☐ Other:

17. If a CONTINUING APPLICATION, check appropriate box and supply the requisite information:[] Continuation [] Divisional [] Continuation-in-part (CIP) of prior application No: 1**18. CORRESPONDENCE ADDRESS**

STAAS & HALSEY LLP
Attn: H. J. Staas
700 Eleventh Street, N.W., Suite 500
Washington, DC 20001

Telephone: (202) 434-1500
Facsimile: (202) 434-1501

COMMUNICATION CONTROL DEVICE

BACKGROUND OF THE INVENTION

5 1. Field of the Invention

The present invention relates to a communication control device which controls communication performed over a communication line.

10 2. Description of the Related Art

Traditionally, input/output devices (each hereinafter called an I/O device) such as communication control devices connected to a computer have had be designed to match the system bus internal to the computer, and a change in the system bus architecture has
15 required an overall change in the design of the I/O devices.

Further, when the system configuration is fixed, if the system is to be constructed in a dual configuration for enhanced reliability, a large-scale
20 configuration has had to be employed, requiring, for example, complete duplication of the computer itself.

On the other hand, in the field of personal computers (PCs), USB (Universal Serial Bus) and IEEE 1394 have been standardized in recent years as interface
25 standards for interfacing peripheral devices to personal computers. These are next-generation serial interfaces that are expected to replace the traditional RS232C, and support "Hot Plug In", "Plug and Play", "Isochronous Transfer", etc.

30 "Hot Plug In" is a function that enables a device to be connected without having to turn the system off, while "Plug and Play" is a function by which a device is just connected to a personal computer and is automatically configured to be ready for use without
35 going through cumbersome installation procedures. Further, isochronous transfer makes possible, for example, the transmission of audio and video signals that

cannot tolerate dropouts, by guaranteeing transmission bandwidth and giving higher data transmission priority.

SUMMARY OF THE INVENTION

5 The present invention has been devised in view of the advent of the above-mentioned next-generation serial interfaces, and an object of the invention is to provide a communication control device which comprises a plurality of communication adapters connected to a serial bus as an external bus, and whose configuration is
10 capable of being changed flexibly without being affected by computer internal bus specifications, etc.

To achieve the above object, according to the present invention, there is provided a communication control device comprising: a plurality of layer control
15 devices, each implementing part of protocol layer functions and together supporting a communication protocol; and a transmission line for interconnecting the plurality of layer control devices to enable data communication between the layer control devices.

20 Preferably, according to the present invention, there are provided a plurality of physical layer control devices, each implementing the function of a different physical layer, and one of the physical layer control devices is dynamically selected when performing
25 communication.

Also preferably, according to the present invention, a physical layer control device for implementing the function of a physical layer is provided which is duplicated by another physical layer control device, and
30 in the event of a failure of one physical layer control device, the other physical layer control device is switched in for operation.

Also preferably, according to the present invention, a program necessary for the operation of each of the
35 layer control devices is downloaded to the corresponding layer control device.

Preferably, according to the present invention, the

transmission line is a serial bus.

Preferably, according to the present invention, the serial bus is compliant with the USB standard.

Also preferably, according to the present invention,
5 the serial bus is compliant with the IEEE 1394 standard.

BRIEF DESCRIPTION OF THE DRAWINGS

Further features and advantages of the present invention will be apparent from the following description with reference to the accompanying drawings, in which:

10 Figure 1 is a block diagram showing the configuration of one embodiment of a communication control device according to the present invention;

Figure 2 is a flowchart for explaining the operation of a computer and each communication adapter;

15 Figure 3 is a block diagram for explaining in further detail an embodiment that uses USB;

Figure 4 is another block diagram for explaining in further detail an embodiment that uses USB;

20 Figure 5 is a block diagram for explaining an embodiment that achieves increased fault tolerance by duplication of communication adapters;

Figure 6 is a block diagram for explaining another embodiment relating to the duplication of communication adapters;

25 Figure 7 is a block diagram for explaining another embodiment which performs a dynamic selection of a physical medium; and

30 Figure 8 is a block diagram for explaining still another embodiment which performs a dynamic selection of a physical medium.

DESCRIPTION OF THE PREFERRED EMBODIMENTS

Embodiments of the present invention will be described below with reference to the accompanying drawings.

35 Figure 1 is a block diagram showing the configuration of one embodiment of a communication control device according to the present invention. A

computer 10 is equipped with a LAN port 12 used for communication over a local area network (LAN) and a serial port 14 used for connecting a serial bus 16 that complies with the USB or the IEEE 1394 standard.

5 Externally to the computer 10, communication adapters 20, 21, 22, 23, 24, and 25 are connected to the serial bus 16. These communication adapters can be classified into the following two categories. That is, the communication adapters 20, 21, 22, and 23 are each
10 provided with an MPU (Micro Processing Unit), a memory, and a serial bus controller. On the other hand, the communication adapters 24 and 25 are each provided with a media controller in addition to an MPU, a memory, and a serial bus controller.

15 Generally, in the case of USB, devices are connected in a tree configuration with a host at its center, and each device is controlled via the host and cannot by itself exchange data with the other devices. On the other hand, in the case of IEEE 1394, both daisy chained
20 and tree connections are possible; there is no host-device relationship, and so-called peer-to-peer communication can be realized.

 In the system configuration shown in Figure 1, when USB is used, two serial buses are provided since there is
25 a host-device relationship, each communication adapter acting as a device with respect to the computer and as a host or a device with respect to the other adapters.

 Figure 2 is a flowchart for explaining the operation of the computer 10 (host) and each communication adapter
30 (device). The example described here specifically assumes the case of USB. First, when the system is powered up, the host initializes itself, while also performing control for the initialization of each device (step 102). In response to the control of the host, each
35 adapter performs initialization (step 202). This initialization includes the initialization of the serial bus controller (i.e., the general initialization of the

USB ports), the setting of the host-device relationship, the setting of the physical identifier (PID) of the device, etc.

5 Next, a program for implementing part of protocol layer functions is downloaded from the host to each adapter (step 104). By storing the program thus downloaded from the host into the memory, the adapter can act as a layer control device for implementing part of the protocol layer functions (step 204). The program
10 downloading to each adapter is done to install the corresponding protocol program into the corresponding device based on the user defined environment.

15 As the result of the download, the adapter 20 acts, for example, as a layer control device for implementing the function of the protocol layer of TCP/IP (Transmission Control Protocol/Internet Protocol), the adapter 21 as a layer control device for X.25, the adapter 22 as a layer control device for MLP for supporting multi-link connections, the adapter 23 as a
20 layer control device for UI (Unnumbered Information), a format in HDLC (High level Data Link Control), the adapter 24 as a layer control device for X.21 as a first physical layer, and the adapter 25 as a layer control device for ISDN as a second physical layer, as shown in
25 Figure 1. On the other hand, the computer 10, the host, becomes a layer control device for implementing the function of an upper layer in the protocol layer stack using an application program stored in its main memory.

30 Next, environment defining parameters which provide the initial values necessary for the operation of the respective protocol layers are downloaded from the host to the respective adapters (step 106). On the other hand, each adapter performs initialization, such as the initialization of communication buffer management,
35 operating communication ports, etc., based on the environment defining parameters downloaded from the host (step 206).

In this way, the computer 10 and the communication adapters 20, 21, 22, 23, 24, and 25 are configured as a communication control device comprising a plurality of layer control devices and together supporting a communication protocol, the communication control device thus being readied to process communications. With each device controlling its associated protocol layer, various kinds of communication processing are performed (steps 108 and 208). This communication processing continues until an end instruction is detected (steps 110 and 210).

The communication processing performed in steps 108 and 208 will be described in detail below. First, the transmit operation is initiated when the application program stored in the computer 10, the host, for implementing the upper layer in the protocol layer stack, is activated.

Supposing, for example, that in the definition of the environment, the protocol stack is defined as consisting of

- (1) Application
- (2) TCP/IP
- (3) HDLC (UI)
- (4) Physical layer (ISDN)

from the upper to lower layers in this order, the application in the computer 10 sends out data via the serial bus 16 to the communication adapter 20 which supports TCP/IP. Next, the communication adapter 20, after processing the received data, passes the processed data via the serial bus 16 to the communication adapter 23 which supports HDLC (UI). The communication adapter 23, after processing the received data, passes the processed data via the serial bus 16 to the communication adapter 25 which supports the physical layer (ISDN). Finally, the communication adapter 25, after processing the received data, sends out the processed data onto the ISDN.

In the receive operation, the above process is

reversed, that is, data is processed in the order of the communication adapter 25 that supports the physical layer (ISDN), the communication adapter 23 that supports UI, the communication adapter 20 that supports TCP/IP, and the computer 10 that stores the application.

On the other hand, when the protocol stack is defined as comprising

- (1) Application
- (2) TCP/IP
- (3) X.25
- (4) MLP
- (5) HDLC (UI)
- (6) Physical layer (X.21)

from the upper to lower layers in this order, the communication adapters supporting the respective protocol layers perform the respectively assigned processing tasks in sequence; in this case, communication can be performed over a packet network connected to the communication adapter 24 that supports X.21 as the first physical layer.

In this way, since the respective protocol layers are assigned to the respective communication adapters interconnected via the common serial interface, a communication control device can be achieved that is virtually unaffected by the bus control or system changes of the computer. Furthermore, dynamic selection of a physical layer, that is, a physical medium, becomes possible.

As noted previously, in the case of the USB, there is a host-device relationship, and peer-to-peer communication between the communication adapters, therefore, cannot be realized. In view of this, configurations using the USB will be described in further detail based on the embodiments shown in Figures 3 and 4.

In Figure 3, the application in the computer 10 as a host exchanges data with a communication adapter 30 that supports TCP/IP and UI, via a serial bus 16a connected to

the serial port 14. Here, the communication adapter 30 supports both the function of the communication adapter 20 and the function of the communication adapter 23 in Figure 1. The communication adapter 30, based on the initially set definition, selects one of two communication lines, a leased line connected to a communication adapter 31 as a first physical layer or a telephone network connected to a communication adapter 32 as a second physical layer. Then, the communication adapter 30 performs communication in a host capacity with the communication adapter 31 or 32 associated with the selected communication line, via a serial bus 16b connected to a serial port provided on the communication adapter 30.

In the embodiment shown in Figure 4, a communication adapter 40 supports TCP/IP and UI, a communication adapter 41 supports X.25 and MLP, a communication adapter 42 supports HDLC and a first physical layer for a leased line, and a communication adapter 43 supports HDLC and a second physical layer for X.21. Based on the definition, the MLP selects the communication line to be used and, in a host capacity, accesses HDLC and other communication line resources in the communication adapter 42 or 43 via an external serial bus 16c. The MLP protocol is thus realized by the plurality of communication adapters 40, 41, 42, and 43 connected to the external serial buses 16a, 16b, and 16c.

Next, referring to the block diagram of Figure 5, a description will be given of an embodiment that achieves increased fault tolerance by duplication of communication adapters connected on a serial bus.

When the computer 10 initializes communication adapters 50, 51, 52, and 53, the communication adapter 50 for implementing the functions of TCP/IP and UI selects, based on the definition and using a line selector 51, either the first physical layer 52 or the second physical layer 53 for connection to the telephone network.

Suppose, for example, that the first physical layer 52 is connected to the telephone network.

Then, the communication is performed by going down the protocol stack

- 5 (1) Application
- (2) TCP/IP, UI
- (3) First physical layer

Here, if the first physical layer 52 is rendered unable to respond or unable to operate reliably because of a
10 hard failure, the communication adapter 50 for implementing the functions of TCP/IP and UI switches the physical layer connected to the telephone network from the first physical layer 52 to the second physical layer 53 by means of the line selector 51, thereby allowing the
15 communication to continue.

As described above, in the embodiment shown in Figure 5, duplication of communication adapters can be easily accomplished for increased fault tolerance, independently of the OS (Operating System), the system
20 bus, etc. of the computer.

While, in the embodiment shown in Figure 5, the line selector as a part of the communication control device is inserted on the serial bus, it will be noted that the duplication can also be accomplished by the configuration
25 shown in Figure 6.

In Figure 6, communication is usually performed using a first communication control device 60. If a failure is detected in the first communication control device 60 during communication, the computer 10 causes a
30 line selection control circuit 63 incorporated therein to send an instruction to a line selector 62 to switch the communication control device connected to the telephone network from the first communication control device 60 to a second communication control device 61. The first and
35 second communication control devices are shown here as representing the layers higher than the physical layer for simplicity.

Next, another embodiment which performs a dynamic selection of a physical medium will be described with reference to Figure 7. In Figure 7, communication is usually performed using a first communication control device 70 connected to the serial bus 16, that is, the communication control device that supports the physical layer for a leased line.

If a failure of a communication adapter or trouble on the transmission line is detected during communication or in a diagnostic test, the computer 10 switches in a second communication control device 71 and selects the ISDN as a backup communication line to restore the communication service. At the remote end which also has the same system configuration, the communication control device that received data over the ISDN reports the status to its host computer, and when a permit is issued from the computer after checking, communication over the ISDN is started.

At the same time, the first communication control device 70, in which a failure was detected, and the corresponding communication device at the remote end move to a diagnostic mode, and communication is started in the diagnostic mode to check hardware replacement and the restoration of the transmission line; if it is confirmed that normal communication is possible as the result of a diagnosis repeated within a specified period, the respective communication control devices notifies the respective host computers accordingly. The system is thus restored by resuming communication over the leased line.

Figure 8 is a block diagram for explaining still another embodiment that performs a dynamic selection of a physical medium. When data is received, an ISDN T-point control device 80 (this is also a communication control device) checks whether the data is analog data or digital data, and sends out the data onto the serial bus 16 after appending an identifier and address to it.

Four communication control devices 81, 82, 83, and 84 are provided: the first and second communication control devices 81 and 82 support communication of analog data, while the third and fourth communication control devices 83 and 84 support communication of digital data. Of these communication control devices 81, 82, 83, and 84, the communication control device having at least either the specified identifier (analog or digital) or the specified address receives the data, performs the necessary processing, and after processing, transfers the data to the computer 10 via the serial bus 16.

The transmit operation is the reverse of the above receive operation. The number of digital communication control devices and the number of analog communication control devices to be installed can be selected in accordance with the number of communication channels and the system configuration.

As described above, according to the present invention, there is provided a communication control device which comprises a plurality of communication adapters connected to a serial bus as an external bus, and whose configuration is capable of being changed flexibly without being affected by internal computer bus specifications, etc.

The invention may be embodied in other specific forms without departing from the spirit or essential characteristics thereof. The present embodiment is therefore to be considered in all respects as illustrative and not restrictive, the scope of the invention being indicated by the appended claims rather than by the foregoing description and all changes which come within the meaning and range of equivalency of the claims are therefore intended to be embraced therein.

What is claimed is:

1. A communication control device comprising:
a plurality of layer control devices, each
implementing part of protocol layer functions and
5 together supporting a communication protocol; and
a transmission line for interconnecting
said plurality of layer control devices to enable data
communication between said layer control devices.
- 10 2. A communication control device, as claimed in
claim 1, wherein a plurality of physical layer control
devices are provided, each implementing the function of a
different physical layer, and one of said physical layer
control devices is dynamically selected when performing
communication.
- 15 3. A communication control device, as claimed in
claim 1, wherein a physical layer control device for
implementing the function of a physical layer is provided
which is duplicated by another physical layer control
device, and in the event of a failure of one physical
20 layer control device, the other physical layer control
device is switched in for operation.
4. A communication control device as claimed in
claim 1, wherein a program necessary for the operation of
each of said layer control devices is downloaded to said
25 each layer control device.
5. A communication control device as claimed in
claim 1, wherein said transmission line is a serial bus.
6. A communication control device as claimed in
claim 5, wherein said serial bus is compliant with the
30 USB standard.
7. A communication control device as claimed in
claim 5, wherein said serial bus is compliant with the
IEEE 1394 standard.

COMMUNICATION CONTROL DEVICE

5

ABSTRACT OF THE DISCLOSURE

Disclosed is a communication control device whose configuration is capable of being changed flexibly without being affected by a computer's internal bus specifications, etc. Externally to the computer, a plurality of communication adapters are connected to a serial bus. This serial bus is compliant with the USB or the IEEE 1394 standard. A program for implementing part of protocol layer functions is downloaded from the computer to each communication adapter. The computer, using an application, implements the function of an upper layer in the protocol layer stack, and the adapters each implement part of the protocol layer functions using the downloaded program, and together they support a communication protocol.

Fig.1




Fig.2




Fig.3




Fig.4




Fig.5




Fig.6




Fig.7





Fig.8



Declaration and Power of Attorney For Patent Application

特許出願宣言書及び委任状

Japanese Language Declaration

日本語宣言書

下記の氏名の発明者として、私は以下の通り宣言します。

As a below named inventor, I hereby declare that:

私の住所、郵便箱、国籍は下記の私の氏名の後に記載された通りです。

My residence, post office address and citizenship are as stated next to my name.

下記の名称の発明に関して請求範囲に記載され、特許出願している発明内容について、私が最初かつ唯一の発明者（下記の氏名が一つの場合）もしくは最初かつ共同発明者であると（下記の名称が複数の場合）信じています。

I believe I am the original, first and sole inventor (if only one name is listed below) or an original, first and joint inventor (if plural names are listed below) of the subject matter which is claimed and for which a patent is sought on the invention entitled

COMMUNICATION CONTROL DEVICE

上記発明の明細書（下記の欄でx印がついていない場合は、本書に添付）は、

the specification of which is attached hereto unless the following box is checked:

☐ 月 日に提出され、米国出願番号または特許協定条約国際出願番号を _____ とし、
(該当する場合) _____ に訂正されました。

☐ was filed on _____
as United States Application Number or
PCT International Application Number
_____ and was amended on
_____ (if applicable).

私は、特許請求範囲を含む上記訂正後の明細書を検討し、内容を理解していることをここに表明します。

I hereby state that I have reviewed and understand the contents of the above identified specification, including the claims, as amended by any amendment referred to above.

私は、連邦規則法典第37編第1条56項に定義されるとおり、特許資格の有無について重要な情報を開示する義務があることを認めます。

I acknowledge the duty to disclose information which is material to patentability as defined in Title 37, Code of Federal Regulations, Section 1.56.

Under the Paperwork Reduction Act of 1995, no persons are required to respond to a collection of information unless it displays a valid OMB control number.

Japanese Language Declaration (日本語宣言書)

私は、米国法典第35編119条(a)-(d)項又は365条(b)項に基づき下記の、米国以外の国の少なくとも一カ国を指定している特許協力条約365(a)項に基づき国際出願、又は外国での特許出願もしくは発明者証の出願についての外国優先権をここに主張するとともに、優先権を主張している、本出願の前に出願された特許または発明者証の外国出願を以下に、枠内をマークすることで、示しています。

Prior Foreign Application(s)

外国での先行出願

11-066589(Pat. Appln.)

(Number)
(番号)

Japan

(Country)
(国名)

12/March/1999

(Day/Month/Year Filed)
(出願年月日)

Priority Not Claimed

優先権主張なし

☐

(Number)
(番号)

(Country)
(国名)

(Day/Month/Year Filed)
(出願年月日)

☐

私は、第35編米国法典119条(e)項に基づいて下記の米国特許出願規定に記載された権利をここに主張いたします。

(Application No.)
(出願番号)

(Filing Date)
(出願日)

(Application No.)
(出願番号)

(Filing Date)
(出願日)

私は、下記の米国法典第35編120条に基づいて下記の米国特許出願に記載された権利、又は米国を指定している特許協力条約365条(c)に基づき権利をここに主張します。また、本出願の各請求範囲の内容が米国法典第35編112条第1項又は特許協力条約で規定された方法で先行する米国特許出願に開示されていない限り、その先行米国出願の提出日以降で本出願書の日本国内または特許協力条約国際提出日までの期間中に入手された、連邦規則法典第37編1条56項で定義された特許資格の有無に関する重要な情報について開示義務があることを認識しています。

(Application No.)
(出願番号)

(Filing Date)
(出願日)

(Status: Patented, Pending, Abandoned)
(現況: 特許許可済、係属中、放棄済)

(Application No.)
(出願番号)

(Filing Date)
(出願日)

(Status: Patented, Pending, Abandoned)
(現況: 特許許可済、係属中、放棄済)

私は、私自身の知識に基づいて本宣言書で私が行なう表明が真実であり、かつ私の入手した情報と私の信じることに基づき表明が全て真実であると信じていること、さらに故意になされた虚偽の表明及びそれと同等の行為は米国法典第18編第1001条に基づき、罰金または拘禁、もしくはその両方により処罰されること、そしてそのような故意による虚偽の表明を行えば、出願した、又は発明者証にされた特許の有効性が失われることを認識し、よってここに上記のごとく宣誓を致します。

I hereby declare that all statements made herein of my own knowledge are true and that all statements made on information and belief are believed to be true; and further that these statements were made with the knowledge that willful false statements and the like so made are punishable by fine or imprisonment, or both, under Section 1001 of Title 18 of the United States Code and that such willful false statements may jeopardize the validity of the application or any patent issued thereon.

Under the Paperwork Reduction Act of 1995, no persons are required to respond to a collection of information unless it displays a valid OMB control number.

Japanese Language Declaration (日本語宣言書)

委任状: 私は下記の発明者として、本出願に関する一切の
手続を米特許審議局に対して遂行する弁理上または代理人
として、下記の者を指名いたします。(弁理上、または代理
人氏名及び登録番号を明記のこと)

POWER OF ATTORNEY: As a named inventor, I hereby appoint
the following attorney(s) and/or agent(s) to prosecute this
application and transact all business in the Patent and Trademark
Office connected therewith (list name and registration number)

James D. Halsey, Jr., 22,729; Harry John Staas, 22,010; David M. Pitcher, 25,908; John C. Garvey, 28,607; J. Randall Beckers, 30,358;
William F. Herbert, 31,024; Richard A. Gollhofer, 31,106; Mark J. Henry, 36,162; Gene M. Garner II, 34,172; Michael D. Stein, 37,240; Paul
I. Kravetz, 35,230; Gerald P. Joyce, III, 37,648; Todd E. Marlette, 35,269; Harlan B. Williams, Jr., 34,756; George N. Stevens, 36,938;
Michael C. Soldner, P-41,455 and William M. Schertler, 35,348 (agent)

書類送付先

Send Correspondence to:

STAAS & HALSEY
700 Eleventh Street, N.W.
Suite 500
Washington, D.C. 20001

直接電話連絡先 (名前及び電話番号)

Direct Telephone Calls to: (name and telephone number)

STAAS & HALSEY
(202) 434-1500

唯一または第一発明者名	Full name of sole or first inventor		
	Masahiro Ichimi		
発明者の署名	日付	Inventor's signature	Date
		Masahiro Ichimi	February 9, 2000
住所	Residence		
	Kawasaki-shi, Kanagawa, Japan		
国籍	Citizenship		
	Japanese		
私書箱	Post Office Address		
	c/o FUJITSU LIMITED, 1-1, Kamikodanaka 4-chome, Nakahara-ku, Kawasaki-shi, Kanagawa 211-8588, Japan		
第二共同発明者	Full name of second joint inventor, if any		
第二共同発明者	日付	Second inventor's signature	Date
住所	Residence		
国籍	Citizenship		
私書箱	Post Office Address		

(第三以降の共同発明者についても同様に記載し、署名をす
ること)

(Supply similar information and signature for third and subsequent
joint inventors.)